

CLAIMS

What is claimed is:

- 5 1. A method for fabricating a flash memory device comprising:
 fabricating a gate structure comprising a tunnel oxide layer, a floating gate layer, an oxide layer,
 and a control gate layer on a semiconductor substrate; and
 repairing said tunnel oxide layer using a rapid thermal oxidation (RTO) process.
- 10 2. The method as recited in Claim 1, further comprising:
 creating a first impurity concentration in said semiconductor substrate prior to said repairing; and
 creating a second impurity concentration in said semiconductor substrate prior to said repairing.
3. The method as recited in Claim 2, wherein said fabricating comprises fabricating a gate
15 structure that is less than 0.21 microns (0.21 μ) in length.
4. The method as recited in Claim 1, wherein said repairing comprises:
 creating additional oxide material in a damaged region of said oxide layer.
- 20 5. The method as recited in Claim 1, wherein said rapid thermal oxidation process
 comprises exposing said semiconductor structure to a temperature of 1000° C for a period of time not
 longer than 20 seconds.
6. The method as recited in Claim 1, wherein said rapid thermal oxidation process
25 comprises selecting a plurality of process parameters wherein a portion of said tunnel oxide layer retains a
 uniform profile after said rapid thermal process is performed.
7. A method for fabricating a memory device comprising:
 fabricating a gate structure upon a semiconductor substrate;
30 depositing a dopant in a first region of said semiconductor substrate and in a second region of
 said semiconductor substrate; and
 performing a rapid thermal oxidation (RTO) process upon said semiconductor substrate.

8. The method as recited in Claim 7, wherein said memory device comprises a flash memory device and comprising fabricating a floating gate memory structure upon said semiconductor substrate.

5

9. The method as recited in Claim 8, wherein said fabricating comprises fabricating a floating gate structure that is than 0.21 microns (0.21μ) in length.

10. The method as recited in Claim 7, wherein said performing a rapid thermal oxidation process comprises creating additional oxide material in a damaged region of an oxide layer of said floating gate structure.

11. The method as recited in Claim 11, wherein said rapid thermal oxidation process comprises selecting a plurality of process parameters wherein a portion of said tunnel oxide layer retains a uniform profile after said rapid thermal process is performed.

15

12. The method as recited in Claim 11, wherein said rapid thermal oxidation process comprises exposing said semiconductor structure to a temperature of 1000°C for a period of time not longer than 20 seconds.

20

13. A method for fabricating a memory device comprising:
depositing a plurality of layers upon a semiconductor substrate;
patterning said plurality of layers to create a stack gate; and
performing a rapid thermal oxidation (RTO) upon said stack gate.

25

14. The method as recited in Claim 13, further comprising:
creating a source region wherein a first impurity concentration is deposited in said semiconductor substrate; and

creating a drain region wherein a second impurity concentration is deposited said semiconductor substrate.

30

15. The method as recited in Claim 14, wherein said patterning comprises creating a stack gate upon said semiconductor substrate that is less than 0.21 microns (0.21μ) in length.

5 16. The method as recited in Claim 13, wherein said performing a rapid thermal oxidation comprises:
creating additional oxide material in a damaged region of an oxide layer of said stack gate.

10 17. The method as recited in Claim 16, wherein said rapid thermal oxidation process comprises selecting a plurality of process parameters wherein a portion of said tunnel oxide layer retains a uniform profile after said rapid thermal process is performed.

15 18. The method as recited in Claim 17, wherein said rapid thermal oxidation process comprises exposing said semiconductor structure to a temperature of 1000°C for a period of time not longer than 20 seconds.